

D-SERIES OPTIONS



The D-Series consists of robust, reliable and energy-efficient ovens with double temperature sensors to ensure an even heat distribution throughout the oven interior, which gives excellent baking results. The model selection is broad, which makes the series suitable for different types and sizes of bakery. The deck oven is also modular, allowing the possible addition of up to five decks.



D-SERIES OPTIONS

OPTIONS DECK OVEN

	D1	D2	D2E	D3	D4
SD Touch II control panel per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Crown height 8.7" per deck (standard 6.3")	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Built-in steam generator with steam trap per deck, 1.8 kW per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Common water connection per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Stone sole per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Door Solid per deck (no window)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Door Solid high oven chamber per deck (no window)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Door with double-glazed window per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Door with double-glazed window high oven chamber per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
High-temperature model incl. 662°F-proof ceramic glass in doors per deck. Can not be combined with double glass	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	
High-temperature model for high oven chamber incl. 662°F-proof ceramic glass in doors per deck. Can not be combined with double glass	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	
Pull-out shelf	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	
Fixed utility shelf	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	
Canopy	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Stainless steel baking chamber per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Condensation unit with canopy	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

IF SEPARATE DECKS ARE ORDERED

	D1	D2	D2E	D3	D4
Separate deck section for extension of existing oven	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Extra kit: Top and bottom	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Extra kit: Top and bottom, SD Touch II	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

ACCESSORIES

	D1	D2	D2E	D3	D4
Oven Loader Liftmatic-G		<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Manual Oven Loader	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Transport trolley in s/s with 10 shelves	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

OPTIONS DOUBLE DEPTH DECK OVEN

	D12ED	D22ED	D32ED	D42ED
SD Touch II control panel per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Canopy	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Door with double-glazed window per deck	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Solid door per deck (no window)	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

ACCESSORIES

	D12ED	D22ED	D32ED	D42ED
Oven Loader Liftmatic-G	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Manual Oven Loader 2 × 600 × 1640 mm	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>
Trolley for Manual Oven Loader 600 × 1640 mm	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input type="radio"/>

- Standard
- Options